Page of
After recording return to:
PO 927 CHILODON OR 9 624

2008-009786 Klamath County, Oregon

00049353200800097860040048

07/08/2008 07:59:58 AM

Fee: \$36.00

RESTRICTIVE COVENANT Fire Siting Standards

The undersigned, being the record owners of all of the real property described as follows See exhibit A and further identified by "Exhibit A" attache
hereto, do hereby make the following restrictive covenant(s) for the above-described real property, specifying that the
covenant(s) shall run with the land and shall be binding on all persons claiming under such land, and that these restriction
shall be for the benefit of and limitation on all future owners of said real property.
In consideration of approval by Klamath County, Oregon of a land use permit to construct a single family dwelling on propert designated by the Klamath County Assessor's Office as Tax Lot <u>500</u> in Township <u>35</u> South, Range <u>7</u> Easi Section <u>1</u> , the following restrictive covenant(s) hereafter bind the subject property:
1. All new dwellings shall comply with the following:
All structural developments shall have a dependable supply of water adequate for normal daily consumption and

All structural developments shall have a dependable supply of water adequate for normal daily consumption and peak emergency needs. The applicant shall provide evidence that the domestic water supply is from a source authorized in accordance with OAR 690, Division 10 and OAR 690, Division 20 and that any surface water used is not from a Class II stream as defined in OAR 629-24-101 (3).

Individual residences where a permanent source of water with a capacity of 4000 gallons or more at the lowest flow such as a stream, pond, or lake exists within 500 feet of the homesite, road access shall be provided to within 15 feet of the water's edge. Access to water shall be not less than 15 feet wide, shall be an improved and maintained surface and shall have an improved vehicle turning area of sufficient size to accommodate local fire protection equipment.

Where residences are supplied with individual water systems without a permanent source of water for fire suppression, the following standards shall apply:

At least one 1 inch standpipe shall be provided at least 50 feet from a building and shall have adequate protection from freezing weather. A standpipe shall be located no greater than 10 feet from any driveway.

Electrical service to a well pump shall be from independent service drops that do not pass through or onto any building.

- 2. Road access to new dwellings shall, at a minimum, meet the following standards:
 - A. Maximum grade shall not exceed 10 percent.
 - B. Road surface must be a minimum of 20 feet wide, all weather surface capable of supporting a fire apparatus at 60,000 lbs.

- C. The entire right-of-way shall be maintained as a fuel break free of brush and other flammable material.
- D. The length of cul-de-sacs shall not exceed 700 feet.
- E. Cul-de-sacs shall have a right-of-way with a 50 foot radius and an improved vehicle turning area not less than 80 feet in diameter.
- F. Bridges or culverts shall have a minimum load limit of 40,000 lbs (20 ton) and shall not be narrower than the improved travel surface serving each end.
- 3. Construction of new dwellings and other structures shall meet the following standards:
 - A. Roofing materials shall carry a minimum of Class B rating. In areas of extreme fire hazard rating, Class A rated roof shall be required.
 - B. Manufactured homes shall be fully skirted from the floor-line to the ground-line. Vents or openings in skirting shall be screened with corrosion-resistant mesh with a mesh size not greater than ½ inch.
 - C. All dwellings shall install a spark arrest on all chimneys. It shall be constructed of nonflammable, corrosive-resistant material. The opening in the mesh shall be no larger than ½ inch.
 - 4. Property fuel breaks, landscaping and maintenance may be planned in accordance with the guidelines found in "Protecting your Home from Wildfire", available from the Planning Department or the Oregon Department of Forestry. The following minimum standards shall apply:
 - A. Primary Fuel Break: all residences shall create and maintain a primary fuel break not less than 30 feet in width extending from the wall line of the structure. Primary fuel breaks consist of vegetation less than 3 inches high. Isolated landscape trees are acceptable if no branches overhang. Trees shall be thinned to 15 feet between tree crowns, and dead limbs near or over-hanging any structure shall be removed.
 - B. Secondary Fuel Break: beyond a primary fuel break, residences shall create and maintain a secondary fuel break not less than 70 feet wide on the down-slope side of a residence and 35 feet on all other sides. Extend the fuel break to 100 feet on the downhill side where steep slopes or dense vegetation are present. Secondary fuel breaks consist of live trees and shrubbery pruned to reduce the possibility of fire reaching roofs of structures or the crowns of trees. Low-growing plants and grasses are to be maintained to prevent the buildup of flammable fuels.
 - C. Wherever practicable, fences shall be constructed of nonflammable materials and maintained to eliminate the buildup of flammable refuse.

- D. Outbuildings and accessory structures will meet the same standards as the residence or primary structure in terms of building construction and fuel breaks.
- 5. Home identification signs shall be posted at the nearest county, state or federal road serving the residence, and shall comply with the Klamath county house numbering system in existence. Home identification signs may be constructed of nonflammable materials with letters at least 3 inches high, ½ inch line width, and a reflective color that contrasts sharply with the background of both the sign itself and the surrounding vegetation.
- 6. In areas subject to the State Scenic Waterway Program, compliance with the primary and secondary fuel-free building setback requirements of this agreement may be modified to comply with specific siting standards contained in a state approved Scenic Waterway Management Program when such regulations conflict.

This covenant shall not be modified or terminated except by the express written consent of the owners of the land at the time, and the Klamath County Community Development Department, as hereafter provided.

KLAMATH COUNTY, a political subdivision of the State of Oregon, shall be considered a party to this covenant and shall have the right, if it so desires, to enforce any or all of the covenant(s) contained herein by judicial or administrative proceeding. This covenant is made pursuant to the provisions of the Klamath County Land Development Code.

Dated this day of, 20 Record Owner Record Owner
STATE OF OREGON)) ss. County of Klamath)
Personally appeared the above names Russell + Linder Wood and acknowledged the foregoing instrument to be his/her voluntary act and deed before me this Day of July 2008.

OFFICIAL SEAL
ALYSSA BOLES
NOTARY PUBLIC-OREGON
COMMISSION NO. 428933
MY COMMISSION EXPIRES MAY 13, 2012

Notary Public for State of Oregon

My Commission Expires:

Note: A copy of the recorded instrument must be returned to Community Development Planning Dept before permits can be issued.

F:\shared\PLANNING\Planning Forms\Covenant-Fire Siting Standards.doc

A tract of land situated in the SE 1/4 NE 1/4 and the NE 1/4 SE 1/4 of Section 2, Township 35 South, Range 7 East of the Willamette Meridian, in the County of Klamath, State of Oregon, more particularly described as follows:

Beginning at a 5/8 inch iron pin on the intersection of the Westerly right of way line of the County Road (Indian Service Road S-45) and the East-West centerline of said Section 2, from which the East quarter corner of said Section 2 bears North 89 degrees 07' 05" East 275.7 feet; thence Northerly along said right of way line on a curve to the left (radius point bears North 87 degrees 27' 05" West 2814.79 feet, central angle = 01 degree 50' 03") 90.11 feet; thence continuing along said right of way line North 00 degrees 42' 52" East 1152.23 feet to a 5/8 inch iron pin; thence South 89 degrees 07' 56" West 282.53 feet to a 5/8 inch iron pin; thence South 00 degrees 33' 09" West 966.82 feet to a 5/8 inch iron pin on the left bank of Sprague River; thence South 52 degrees West 65 feet, more or less, to the center of said Sprague River; thence Southeasterly along the center of said Sprague River to a point 375.00 feet Southerly (measured at right angles) from the East-West centerline of said Section 2; thence North 89 degrees 07' 05" East 112 feet, more or less, to a 5/8 inch iron pin on the Westerly right of way line of said County road; thence Northerly along said right of way line on a curve to the left (radius point bears North 79 degrees 45' 01" West 2814.79 feet, central angle = 07 degrees 42' 04") 378.34 feet to the point of beginning.

CODE 118 & 138 MAP 3507-200 TL 800 CODE 138 & 118 MAP 3507-200 TL 800

State of Oregon, County of Klamath Recorded 09/27/00, at <u>多らしず</u>, m. In Vol. M00 Page <u>35389</u> Linda Smith, County Clerk Fee\$ <u>2</u>6