Page of					
After recording return to:					
Tru-Line Surveying Inc. 2333 Summers Lane					
Klamath Falls OR 97603					

Returned @ Counter

2009-000289 Klamath County, Oregon

00058545200900002890040041
----------------------------

01/12/2009 09:02:31 AM

Fee: \$36.00

## RESTRICTIVE COVENANT

Fire Siting Standards								
Land 1	undersigned, bein Partition 33 - 0	ું ક	record	owners	of	all	of	the real property described as follows; and further identified by "Exhibit A" attached
covenan	nt(s) shall run with the for the benefit of an	ne land an	d shall be	e binding	on all	perso	ons c	above-described real property, specifying that the claiming under such land, and that these restrictions roperty.
iesignat	deration of approval ted by the Klamath , the follow	County Ass	sessor's (	Office as	ax Lo	ot. 10	סנ	rmit to construct a single family dwelling on property _ in Township <u>38</u> South, Range <u>11 ½</u> East, subject property:
1. A	All new dwellings sha	all comply v	with the fo	ollowing:				
	All structural develo	pments sha	all have a	dependal	ble su	pply c	of wat	ter adequate for normal daily consumption and
ţ	peak emergency ne	eds. The a	applicant :	shall provi	de ev	idenc	e tha	at the domestic water supply is from a source
	authorized in accord is not from a Class I							0, Division 20 and that any surface water used
				•		•	•	apacity of 4000 gallons or more at the lowest
								nomesite, road access shall be provided to
								ss than 15 feet wide, shall be an improved and
								ea of sufficient size to accommodate local fire
	protection equipmen		avo un m	proved ve	, noic	turi ili	ıy alt	sa of sufficient size to accommodate local tire
-	• •		with indi	vidual wat	or eve	tome	sacith c	out a permanent source of water for fire
	suppression, the follo				ei bys	nems	WILLIC	but a permanent source of water for fire
	• • • • •	<b>-</b>						

At least one 1 inch standpipe shall be provided at least 50 feet from a building and shall have adequate protection from freezing weather. A standpipe shall be located no greater than 10 feet from any driveway.

Electrical service to a well pump shall be from independent service drops that do not pass through or onto any building,

- 2. Road access to new dwellings shall, at a minimum, meet the following standards:
  - A. Maximum grade shall not exceed 10 percent.
  - B. Road surface must be a minimum of 20 feet wide, all weather surface capable of supporting a fire apparatus at 60,000 lbs.

- C. The entire right-of-way shall be maintained as a fuel break free of brush and other flammable material.
- D. The length of cul-de-sacs shall not exceed 700 feet.
- E. Cul-de-sacs shall have a right-of-way with a 50 foot radius and an improved vehicle turning area not less than 80 feet in diameter.
- F. Bridges or culverts shall have a minimum load limit of 40,000 lbs (20 ton) and shall not be narrower than the improved travel surface serving each end.
- 3. Construction of new dwellings and other structures shall meet the following standards:
  - A. Roofing materials shall carry a minimum of Class B rating. In areas of extreme fire hazard rating, Class A rated roof shall be required.
  - B. Manufactured homes shall be fully skirted from the floor-line to the ground-line. Vents or openings in skirting shall be screened with corrosion-resistant mesh with a mesh size not greater than ½ inch.
  - C. All dwellings shall install a spark arrest on all chimneys. It shall be constructed of nonflammable, corrosive-resistant material. The opening in the mesh shall be no larger than ½ inch.
  - 4. Property fuel breaks, landscaping and maintenance may be planned in accordance with the guidelines found in "Protecting your Home from Wildfire", available from the Planning Department or the Oregon Department of Forestry. The following minimum standards shall apply:
  - A. Primary Fuel Break: all residences shall create and maintain a primary fuel break not less than 30 feet in width extending from the wall line of the structure. Primary fuel breaks consist of vegetation less than 3 inches high. Isolated landscape trees are acceptable if no branches overhang. Trees shall be thinned to 15 feet between tree crowns, and dead limbs near or over-hanging any structure shall be removed.
  - B. Secondary Fuel Break: beyond a primary fuel break, residences shall create and maintain a secondary fuel break not less than 70 feet wide on the down-slope side of a residence and 35 feet on all other sides. Extend the fuel break to 100 feet on the downhill side where steep slopes or dense vegetation are present. Secondary fuel breaks consist of live trees and shrubbery pruned to reduce the possibility of fire reaching roofs of structures or the crowns of trees. Low-growing plants and grasses are to be maintained to prevent the buildup of flammable fuels.
  - C. Wherever practicable, fences shall be constructed of nonflammable materials and maintained to eliminate the buildup of flammable refuse.

- D. Outbuildings and accessory structures will meet the same standards as the residence or primary structure in terms of building construction and fuel breaks.
- 5. Home identification signs shall be posted at the nearest county, state or federal road serving the residence, and shall comply with the Klamath county house numbering system in existence. Home identification signs may be constructed of nonflammable materials with letters at least 3 inches high, 1/2 inch line width, and a reflective color that contrasts sharply with the background of both the sign itself and the surrounding vegetation.
- 6. In areas subject to the State Scenic Waterway Program, compliance with the primary and secondary fuel-free building setback requirements of this agreement may be modified to comply with specific siting standards contained in a state approved Scenic Waterway Management Program when such regulations conflict.

This covenant shall not be modified or terminated except by the express written consent of the owners of the land at the time. and the Klamath County Community Development Department, as hereafter provided.

KLAMATH COUNTY, a political subdivision of the State of Oregon, shall be considered a party to this covenant and shall have the right, if it so desires, to enforce any or all of the covenant(s) contained herein by judicial or administrative proceeding. This covenant is made pursuant to the provisions of the Klamath County Land Development Code.

Dated this M. day of June 20 05.	
Record Owner Robert S. Johnson	Record Owner
STATE OF OREGON ) State of Klameth (W )	
	Johnson and acknowledged the
oregoing instrument to be his/her voluntary act and deed be	Notary Public for State of Oregen Halvaji Cu
	My Compliant Fundament

CHYRELLE L. WILLIAMS My commission expires 1/5/2011

My Commission Expires:

Vote: A copy of the recorded instrument must be returned to Community Development Planning Dept before permits can be ssued.

F:\shared\PLANNING\Planning Forms\Covenant-Fire Siting Standards.doc

## Exhibit "A"

Being Government lots 1 and 2 and the Southeast quarter of the Northeast quarter of section 2, Township 38 South, Range 11 ½ EWM, Klamath County, Oregon.