Page _1_ of	
After recording return to:	
Lloyd Park	

2010-005174 Klamath County, Oregon

00083441201000051740040040

05/03/2010 11:17:28 AM

Fee: \$52.00

## RESTRICTIVE COVENANT Fire Siting Standards

In consideration of approval by Klamath County, Oregon of a land use permit to develop on property designated by the Klamath County Assessor's Office as Tax Lot 600 in Township South, Range 13 East, Section 9, the following restrictive covenant(s) hereafter bind the subject property:

- 1. All new development shall comply with the following:
  - A. Provide a dependable supply of water adequate for normal daily consumption and peak emergency needs from a source authorized in accordance with Oregon Administrative Rule (OAR) and that any surface water used is not from a Class II stream.
  - B. Provide for and make available a permanent source of water with a capacity of 4000 gallons or more. If a stream, pond, or lake exists within 500 feet of the homesite a road access shall be provided to within 15 feet of the water's edge. Access to water shall be not less than 15 feet wide and shall be an improved and maintained surface with an improved vehicle turning area of sufficient size to accommodate local fire protection equipment.
  - C. Where residences are supplied with individual water systems without a permanent source of water for fire suppression (e.g., fire hydrants), the following standards shall apply:
    - a. At least one 1 inch hydrant standpipe shall be provided at least 50 feet from a building and no greater distance than 10 feet from the driveway with adequate protection from freezing weather.
    - b. Electrical service to a well pump shall not pass through, under, or onto any non-well protecting structure.
- 2. Road access shall meet the following minimum standards:
  - A. Maximum grade shall not exceed 10 percent.
  - B. Road surface must be a minimum of 20 feet wide with an all weather surface capable of supporting a fire apparatus at 60,000 lbs minimum or as prescribed by the Fire Marshall.

- C. The entire legal access way shall be maintained, at all times, as a fuel break free of brush and other flammable material.
- D. The length of cul-de-sacs shall not exceed 700 feet and have a right-of-way with a 50 foot radius with an improved vehicle turning area not less than 80 feet in diameter.
- E. Installation of bridges or culverts shall have a minimum load limit of 40,000 lbs (20 ton) and not be narrower than the improved travel surface serving each end.
- 3. All structures shall be constructed to the following standards:
  - A. Roofing materials shall carry a minimum of Class B rating. In areas of extreme fire hazard rating, Class A rated roof shall be required.
  - B. The siting of a manufactured home shall require fully skirting from the floor-line to the ground-line with vents or openings screened with corrosion-resistant mesh not greater than ¼ inch size.
  - C. All chimneys shall have spark arrest installed with nonflammable, corrosive-resistant material having opening in the mesh no larger than ¼ inch.
- 4. Property fuel breaks, landscaping and maintenance may be planned in accordance with the following minimum standards:
  - A. A Primary Fuel Break shall be created and maintained no less than 30 feet in width extending from the wall line of any structure. Vegetation shall be less than 3 inches high, at all times. All trees within the primary break shall be thinned to 15 feet between tree crowns, and dead limbs near or over-hanging any structure shall be removed at all times.
  - B. A Secondary Fuel Break shall be created and maintained no less than 70 feet wide on the down-slope side of a residence and 35 feet on all other sides. Extend the fuel break to 100 feet on the downhill side where steep slopes or dense vegetation are present. Live trees and shrubbery shall be pruned to reduce the possibility of fire reaching roofs of structures or the crowns of trees. Low-growing plants and grasses shall be maintained to prevent the buildup of flammable fuels.
  - C. Fences shall be constructed of nonflammable materials and maintained to eliminate the buildup of flammable refuse.
- 5. Home identification signs shall be posted at the nearest county, state or federal road serving the residence; and, constructed of nonflammable materials with letters at least 3 inches high, ½ inch line width; and, with a reflective color that contrasts sharply with the background of both the sign itself and the surrounding vegetation.

This covenant shall not be modified or terminated except by the express written consent of the owners of the land at the time, and the Klamath County Planning Department, as hereafter provided.

KLAMATH COUNTY, a political subdivision of the State of Oregon, shall be considered a party to this covenant and shall have the right, if it so desires, to enforce any or all of the covenant(s) contained herein by judicial or administrative proceeding. This covenant is made pursuant to the provisions of the Klamath County Land Development Code.

	, 20 <u>/ O</u> .
How Parler Record Owner	Record Owner
Alney Rost	Record Owner
STATE OF OREGON ) )ss. County of Klamath )	
Personally appeared the above named persons and a be his/her voluntary act and deed before me this $\frac{Z-M}{2}$	acknowledged the foregoing instrument to day of 10 H y 20 10
BY DEBORAH SCHAAF	
OFFICIAL SEAL  DEBORAH E SCHAAF  NOTARY PUBLIC - OREGON  COMMISSION NO. 441334	Notary Public for State of Oregon  My Commission Expires:

**Note** A copy of the recorded instrument must be returned to Klamath County Planning Department before development permits can be issued.

## **EXHIBIT A**

That parcel conveyed to Grantors at Document 2007-003508 recorded on March 1, 2007 Klamath County Records. This parcel is further described as:

North Half of the North Half of the Northeast Quarter of the Southeast Quarter of Section 19, Township 35 South, Range 13, East of the Willamette Meridian, in Klamath County, Oregon.

That property conveyed to Grantors at Deed Instrument Recorded at 2007-00518 recorded on January 11, 2007 Klamath County Deed Records, State of Oregon. Further described as:

The S 1/2 N 1/2 NE 1/4 SE 1/4 and the N 1/2 S 1/2 NE 1/4 SE 1/4 of Section 19, Township 35 South, Range 13 East of the Willamette Meridian, Klamath County, Oregon.