



00234084201900001170040046

01/04/2019 12:09:53 PM

Fee: \$97.00

After recording return to:

Sandra Bolyard
34043 Hwy 97N
Chiloquin, OR 97624

RESTRICTIVE COVENANT Fire Hazard Area Siting Standards

In consideration of approval by Klamath County, Oregon of a land use permit, the undersigned,

Sandra Bolyard being the owners of record of all of the
 real property described as follows; R- 3507-01600-00700

and further identified by "Exhibit A" attached hereto, do hereby make the following restrictive covenant(s) for the above-described real property, specifying that the covenant(s) shall run with the land and shall be binding on all persons claiming under such land, and that these restrictions shall be for the benefit of and limitation on all future owners of said real property.

1. All new development shall comply with the following:

- A. Provide a dependable supply of water adequate for normal daily consumption and peak emergency needs from a source authorized in accordance with Oregon Administrative Rule (OAR) and that any surface water used is not from a Class II stream.
- B. Provide for and make available a permanent source of water with a capacity of 4000 gallons or more. If a stream, pond, or lake exists within 500 feet of the homesite a road access shall be provided to within 15 feet of the water's edge. Access to water shall be not less than 15 feet wide and shall be an improved and maintained surface with an improved vehicle turning area of sufficient size to accommodate local fire protection equipment.
- C. Where residences are supplied with individual water systems without a permanent source of water for fire suppression (e.g., fire hydrants), the following standards shall apply:
 - a. At least one 1 inch hydrant standpipe shall be provided at least 50 feet from a building and no greater distance than 10 feet from the driveway with adequate protection from freezing weather.
 - b. Electrical service to a well pump shall not pass through, under, or onto any non-well protecting structure.

2. Road access shall meet the following minimum standards:

- A. Maximum grade shall not exceed 10 percent.
- B. Road surface must be a minimum of 20 feet wide with an all weather surface capable of supporting a fire apparatus at 60,000 lbs minimum or as prescribed by the Fire Marshall.

- C. The entire legal access way shall be maintained, at all times, as a fuel break free of brush and other flammable material.
 - D. The length of cul-de-sacs shall not exceed 700 feet and have a right-of-way with a 50 foot radius with an improved vehicle turning area not less than 80 feet in diameter.
 - E. Installation of bridges or culverts shall have a minimum load limit of 40,000 lbs (20 ton) and not be narrower than the improved travel surface serving each end.
3. All structures shall be constructed to the following standards:
- A. Roofing materials shall carry a minimum of Class B rating. In areas of extreme fire hazard rating, Class A rated roof shall be required.
 - B. The siting of a manufactured home shall require fully skirting from the floor-line to the ground-line with vents or openings screened with corrosion-resistant mesh not greater than ¼ inch size.
 - C. All chimneys shall have spark arrest installed with nonflammable, corrosive-resistant material having opening in the mesh no larger than ¼ inch.
4. Property fuel breaks, landscaping and maintenance may be planned in accordance with the following minimum standards:
- A. A Primary Fuel Break shall be created and maintained no less than 30 feet in width extending from the wall line of any structure. Vegetation shall be less than 3 inches high, at all times. All trees within the primary break shall be thinned to 15 feet between tree crowns, and dead limbs near or over-hanging any structure shall be removed at all times.
 - B. A Secondary Fuel Break shall be created and maintained no less than 70 feet wide on the down-slope side of a residence and 35 feet on all other sides. Extend the fuel break to 100 feet on the downhill side where steep slopes or dense vegetation are present. Live trees and shrubbery shall be pruned to reduce the possibility of fire reaching roofs of structures or the crowns of trees. Low-growing plants and grasses shall be maintained to prevent the buildup of flammable fuels.
 - C. Fences shall be constructed of nonflammable materials and maintained to eliminate the buildup of flammable refuse.
5. Home identification signs shall be posted at the nearest county, state or federal road serving the residence; and, constructed of nonflammable materials with letters at least 3 inches high, ½ inch line width; and, with a reflective color that contrasts sharply with the background of both the sign itself and the surrounding vegetation.

This covenant shall not be modified or terminated except by the express written consent of the owners of the land at the time, and the Klamath County Planning Department, as hereafter provided.

KLAMATH COUNTY, a political subdivision of the State of Oregon, shall be considered a party to this covenant and shall have the right, if it so desires, to enforce any or all of the covenant(s) contained herein by judicial or administrative proceeding. This covenant is made pursuant to the provisions of the Klamath County Land Development Code.

Dated this 4 day of January, 2019.

Sandra Bolyard
Record Owner Sign

Record Owner Sign

Record Owner Sign

Record Owner Sign

STATE OF OREGON)
) ss.
County of Klamath)

Personally appeared the above named persons and acknowledged the foregoing instrument to be his/her voluntary act and deed before me this 4th day of Jan, 2019.

By Sandra Bolyard.

Caroline D. Pendell
Notary Public for State of Oregon



June 16, 2020
My Commission Expires:

Note: A copy of the recorded instrument must be returned to Klamath County Planning Department before development permits can be issued.

EXHIBIT A

(Legal Description, cont.)

33700**PAGE 3:**

A tract of land in Government Lot Numbers 33 and 39 in Section 16, Township 35 South, Range 7 East of the Willamette Meridian, Klamath County, Oregon, more particularly described as follows:

Beginning at the quarter section corner on the South boundary of Section 16, Township 35 South, Range 7 East of the Willamette Meridian, Klamath County, Oregon; thence North along the center line of Section 16, a distance of 1330.0 feet, more or less, to the Northwest corner of Government Lot Number 33, which corner is monumented with a 3/4" iron pipe; thence East along the North boundary of Lot 33, a distance of 323.30 feet, more or less, to a point on the Westerly right of way boundary of U. S. Highway Number 97, which point is monumented with a 3/4" iron pipe; thence South 2 degrees 22' West along said right of way boundary a distance of 333.30 feet to a 3/4" iron pipe marking the Northwest corner of that parcel of land recorded in Volume 363, page 56 of Deed Records of Klamath County, Oregon; thence following along the bounds of said parcel of land, North 62 degrees 07' East, 629.30 feet; East 454.20 feet; South 95.00 feet; and East 107.27 feet; thence leaving said bounds and bearings North 41 degrees 03 1/2' East 155.48 feet to a 1/2" steel rod; thence North 51 degrees 18' West 55.0 feet to a 1/2" steel rod; thence North 45 degrees 50' East 265.4 feet to a 1/2" steel rod marking the true point of beginning of this description; thence North 23 degrees 18' East 158.00 feet to a point; thence South 85 degrees 53' East 679.5 feet, more or less, to the waterline of the Williamson River; thence Southerly along said waterline 100 feet, more or less, to a point, said point being South 65 degrees 07' East 687.3 feet from the point of beginning; thence North 56 degrees 07' West 687.3 feet to the point of beginning.

State of Oregon, County of Klamath
Recorded 08/15/00, at 11:12 a.m.
in Vol. 800 Page 536 77
Linda Smith,
County Clerk Fee \$ 3.00